

Rainier







Flame retardant hi-vis fleece

The flame retardant hi-vis fleece Rainier can be zipped into different jackets thanks to the I.L.S. system. You can wear the fleece separately to protect you from cold and wind. The soft breathable fleece fabric has undergone an anti-pilling treatment which makes it last longer. The fleece, with elastic sleeve ends and an elastic cord in the hem, features two inset pockets with zipper and one inside pocket.







Flame retardant hi-vis fleece

Interior:

» 1 inside pocket

» Fixed flame retardant cotton lining in front

Rainier - 496ZN2TF1

European Standards: (based upon size L)

» EN ISO 14116: 2015 / IND. 1

» EN ISO 20471: 2013 +A1 2016 / Class 2

» EN 14058 : 2017 / Class 11 xx

» EN ISO 13688: 2013

Exterior:

- » Straight collar
- Hidden zip closure
- 2 inset pockets with zip closure
- » Elastic at end of sleeves
- » Elastic drawstring in hem
- » Back length 77 cm (L)

Double sided fleece: 100% flame retardant polyester; ± 275 g/m²

Sizes:

S - XXXL

Colour:

- » 278 Hi-Vis Yellow/Navy
- » 279 Hi-Vis Orange/Navy

I.L.S.:

3073 - 3074 - 3085 - 7222 - 7223 - 7229 - 7237 - 9728

Packaging:

5 pieces per box

Wash and care instructions:











SIOEN head office

Fabriekstraat 23 B-8850 Ardooie Belgium T: +32 (51) 740 800 F: +32 (51) 740 962 www.sioen-ppc.com



Discover our products © 2020 Sioen Apparel - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the Sioen Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice.

All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Sioen disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.